

Appendix E. Figure Descriptions

Appendix E. Figure Descriptions

This appendix includes written descriptions of all figures included in this Technical Report. If needed, additional figure interpretation is available from the ODOT Senior Environmental Project Manager at (503) 731-4804.

Figure Number	Figure Title	Figure Description
1	Project Area	Figure 1 shows the Project Area. The Project Area includes a 1.7-mile segment of Interstate 5 (I-5), beginning north of Interstate 405 (I-405) at milepost 303.2, extending south to the Burnside Bridge just south of Interstate 84 (I-84) at milepost 301.5. The Project Area also includes the interchange of I-5 and N Broadw ay and NE Weidler Street (Broadw ay/Weidler interchange) and the surrounding transportation network, from approximately N/NE Hancock Street to the north, N Benton Avenue to the w est, N/NE Multnomah Street to the south, and NE 2nd Avenue to the east. Figure 1 also shows the Willamette River to the w est of the Project Area and the follow ing four bridges (from north to south): Fremont Bridge, Broadw ay Bridge, Steel Bridge, and Burnside Bridge. The Project Area includes segments of both I-5 and I-84.
2	Auxiliary Lane/ Shoulder Improvements	Figure 2 shows the locations of the proposed auxiliary lanes and shoulder improvements on I-5. One new northbound (NB) auxiliary lane would be added to connect the I-84 w estbound on-ramp to the N Greeley off-ramp. A new southbound (SB) auxiliary lane would extend the existing auxiliary lane that enters I-5 SB from the N Greeley on-ramp. The extent of proposed auxiliary lanes and shoulder improvements begin near where I-5 crosses over N Russell and extends south to I-84. Figure 2 also shows the Project Area.
3	I-5 Auxiliary (Ramp-to- Ramp) Lanes – Existing Conditions and Proposed Improvements	Figure 3 shows the existing and proposed auxiliary lane configurations from the N Greely on-ramp extending south to the SB Morrison Bridge off-ramp. Existing conditions are show n on the left and proposed improvements are show n on the right. Existing SB conditions include tw o SB lanes and three on-ramps (listed from north to south): N Greeley, I-405/N Fremont, and N Wheeler and three off-ramps (listed from north to south): N Broadw ay, I-84, and Morrison Bridge. There are existing auxiliary lanes betw een the N Greeley on-ramp extending to just south of the N Broadw ay off-ramp, the I-405/N Fremont on-ramp and N Broadw ay off-ramp, and N Wheeler on-ramp and I-84 off-ramp. Existing NB conditions include tw o NB lanes and tw o on-ramps (listed from south to north): I-84 and N Broadw ay and tw o off-ramps (listed from south to north): N Weidler, I-405/N Fremont, and N Greeley. There are existing auxiliary lanes betw een the I-84 on-ramp and N Weidler off-ramp and betw een the N Broadw ay on-ramp and I-405/N Fremont off-ramp. For proposed improvements, the on-ramps and off-ramps are the same as those show n for existing conditions, and all existing auxiliary lanes remain. There is one new SB proposed auxiliary lane that results in a continuous auxiliary lane from the N Greeley on-ramp extending south to the Morrison Bridge off-ramp. There is one NB proposed auxiliary lane that results in a continuous auxiliary lane from the Paramp north to the N Greeley off-ramp. Two additional proposed NB auxiliary lane segments also extend the existing auxiliary lane betw een the I-84 on-ramp and N Weidler off-ramp.

Figure Number	Figure Title	Figure Description
4	I-5 Cross Section (N/NE Weidler Overcrossing) – Existing Conditions and Proposed Improvements	Figure 4 shows a cross section comparison of existing and proposed conditions of I- 5 south of the N/NE Weidler overcrossing within the Broadway/Weidler interchange area. Existing conditions are shown on the top and are the same for NB and SB traffic and include an inside and outside shoulder of varying width and two 12-foot lanes. Proposed lane configuration is shown below the existing conditions and is the same for NB and SB traffic and include an inside and outside shoulder, two through lanes, and one auxiliary lane. All shoulders and lanes are 12 feet wide.
5	Broadw ay/ Weidler/ Williams and Vancouver/ Hancock Highw ay Covers	Figure 5 shows a rendering of the Broadw ay/Weidler/Williams and Vancouver/Hancock highway covers. The Broadway/Weidler/Williams cover appears as a green space that spans east-west across I-5, extending from immediately south of N/NE Weidler to immediately north of N/NE Broadway. The entire block between N/NE Weidler, NE Victoria, N/NE Broadway, and N Williams is all show n as a green space covering I-5. The Vancouver/Hancock cover is located farther to the north and appears as a smaller green space extending northwest and southeast from N Vancouver at its intersection with N/NE Hancock. Proposed bike lanes are also show n along N/NE Weidler, N Williams, N Vancouver, N/NE Broadway, and N/NE Hancock.
6	Broadw ay/ Weidler Interchange Area Improvements	Figure 6 show s locations of improvements to the Broadw ay/Weidler interchange betw een I-5, the interchange, and the local street netw ork. Improvements are labeled with letters A through H. The Broadw ay/Weidler/Williams cover spans east- west across I-5, extending from immediately south of N/NE Weidler to immediately north of N/NE Broadw ay. The Vancouver/Hancock cover is located farther to the north and appears as a smaller green space extending northwest and southeast from N Vancouver at its intersection with N/NE Hancock. Both covers are indicated by the letter "A." Letter "B" is located near the bottom of the figure and show s how the I-5 SB on-ramp would be relocated by having it begin one block farther north at NNE Weidler instead of N Ramsay Way, where the existing ramp begins. Letter "C" located near the middle of the figure show s the segment of N Williams betw een N Ramsay and N Weidler that would be closed to private motor vehicles. Letter "D" located near the middle of the figure show s the location of w here traffic flow on N Williams betw een N/NE Weidler and N/NE Broadw ay would be converted to a reverse traffic flow tw o-way street with a 36-foot-wide median. Letter "E" show s the location of the proposed Hancock-Dixon crossing that extends from the intersection of N Dixon and N Wheeler east to N Williams and N/NE Hancock. Letter "G" indicates the location w here N Flint would be removed beginning at N Tillamook and extending south to N Broadw ay. Letter "H" show s the location of the proposed Clackamas bicycle and pedestrian bridge, located south of N/NE Weidler to connect NE Clackamas with N Williams. The Project Area boundary and proposed auxiliary lanes and shoulders are also show non the figure.
7	Conceptual Illustration of Proposed N Williams Multi- Use Path and Revised Traffic Flow	Figure 7 shows a rendering of the proposed N Williams multi-use path and reverse traffic flow. The foreground in the bottom half of the rendering shows the multi-use path as an extension of the sidew alk to the w est (left) of N Williams. The top half of the rendering shows two SB traffic lanes to the east (right) of the multi-use path/median and two NB traffic lanes to the w est (left) of the multi-use path/median. The Broadw ay/Weidler/Williams cover is show n as green space to the east (right) of N Williams SB traffic lanes.
8	Clackamas Bicycle and Pedestrian Crossing	Figure 8 shows a rendering of the Clackamas bicycle and pedestrian crossing. The crossing is show n as a curved elevated path crossing I-5, connecting NE Clackamas on the east side of I-5 to N Williams on the west side of I-5. Green bicycle lanes are also show n on either side of N Williams, located just west of I-5.

Figure Number	Figure Title	Figure Description
9	City and ODOT Stormw ater Outfalls	Figure 9 shows the Project Area, which includes a 1.7-mile segment of I-5, beginning north of I-405 at milepost 303.2, extending south to the Burnside Bridge just south of I-84 at milepost 301.5; City of Portland Bureau of Environmental Services (BES) stormw ater outfalls; and Oregon Department of Transportation (ODOT) stormw ater outfalls. Four BES stormw ater outfalls are show n on the east bank of the Willamette River in the follow ing locations: approximately halfw ay betw een the Fremont and Broadw ay Bridges, approximately halfw ay betw een the Broadw ay and Steel Bridges, near the SB I-5 off-ramp for I-84, and at the Burnside Bridge. Six ODOT stormw ater outfalls are show n on the east bank of the Willamette River in the follow ing locations: Broadw ay Bridge, just north of the BES outfall near the SB I-5 off-ramp for I-84, NB I-5 off-ramp for I-84, just north of the Burnside Bridge, and just south of the Burnside Bridge (tw o outfalls).